

JB4

"JB4": ANSCHLUSSKASTEN MIT SCHUTZ GEGEN ÜBERSPANNUNGEN,
BIS ZU 4 WÄGEZELLEN



Einfacher Anschlusskasten mit 4 Eingängen, Schutzart IP67, ausgestattet mit einer Platine zum Anschluss der Signale von 2, 3 oder 4 Wägezellen. Schraubbare Klemmleisten zum einfachen Anschließen. Die Schutzschaltung schützt vor Blitzen und Überspannungen. Die niedrigen Kosten machen es zur idealen Wahl für statische Wägesysteme wie Silos, Tanks oder Großcontainer.

Die ideale Lösung für
**fortschrittliche industrielle
Anwendungen**

TECHNISCHE EIGENSCHAFTEN

- ABS-Gehäuse. Schutzart IP67.
- Schutzart IP68 bei Vergiessen mit GELBOX Antikondensations-Gel.
- Max. Eingangsspannung: 5VDC.
- Max. Eingangsstrom: 700mA.
- Spitzenimpulsstrom: 15kA.
- Max. Eingangssignal der Wägezelle: 1000mV.
- Temperaturkoeffizient: 50ppm/°C.
- Abmessungen (lxwxh): 120x80x55mm.



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE